

24LC16B-I/ST

Data Sheet

RFO

EEPROM Serial-I2C 16K-bit 8Block x 256 x 8 3.3V/5V 8-Pin TSSOP Tube

Manufacturers	Microchip Technology, Inc	The second secon
Package/Case	TSSOP-8	
Product Type	Memory	
RoHS	Rohs	
Lifecycle		Images are for reference only

Please submit RFQ for 24LC16B-I/ST or Email to us: sales@ovaga.com We will contact you in 12 hours.

General Description

The Microchip Technology Inc. 24AA16/24LC16B is a 16Kb I2CTM compatible Serial EEPROM. The device is organized as eight blocks of 256 x 8-bit memory with a 2-wire serial interface. Low-voltage design permits operation down to 1.7V with standby and active currents of only 1 μ A and 1 mA, respectively. The 24XX16 also has a page write capability for up to 16 bytes of data. The 24XX16 is available in the standard 8-pin PDIP, surface mount SOIC, TSSOP, 2x3 DFN and MSOP packages, and is also available in the 5-lead SOT-23 package.

Features

Single supply with operation down to 2.5V for 24LC16B devices

Low-power CMOS technology

2-wire serial interface, I2CTM compatible

Schmitt Trigger inputs for noise suppression

Output slope control to eliminate ground bounce

100 kHz (2.5V) and 400 kHz clock compatibility

Page write time 5 ms max.

More than 1 million erase/write cycles

Data retention > 200 years

Dolated Droducts



AT24CM02-SSHM-B

Microchip Technology, Inc SOIC-8



24FC512-I/SM

SOIC-8

Microchip Technology, Inc SOIJ-8

AT24C512C-SSHM-T

Microchip Technology, Inc











AT24CM02-SSHD-B

Microchip Technology, Inc SOIC-8

<u>24AA512-I/SM</u>

Microchip Technology, Inc SOIJ-8

24LC256-I/ST

Microchip Technology, Inc TSSOP-8

AT24C04D-MAHM-T

Microchip Technology, Inc UDFN-8



24LC32AT-I/SN Microchip Technology, Inc SOIC-8