🔉 ovaga

AD5245BRJZ10-R2

Data Sheet

Volatile Digital Potentiometer, 10 kohm, Single, I2C, Serial, \pm 30%, 2.7 V

Manufacturers	Analog Devices, Inc
Package/Case	SOT-23-8
Product Type	Data Acquisition - Digital Potentiometers
RoHS	Rohs
Lifecycle	



Images are for reference only

Please submit RFQ for AD5245BRJZ10-R2 or Email to us: sales@ovaga.com We will contact you in 12 hours.

<u>RFQ</u>

General Description

The AD5245 provides a compact 2.9 mm x 3 mm packaged solution for 256 position adjustment applications. This device performs the same electronic adjustment function as a mechanical potentiometer or a variable resistor. The low temperature coefficient makes this device ideal for high accuracy and stability variable resistance adjustments.

The wiper settings are controllable through the I2C compatible digital interface, which can also be used to read back the present wiper register control word.

Operating from a 2.7 to 5.5 volt power supply consuming less than 5 µA allows for usage in portable battery operated applications.

Features	Application
256 Position	Mechanical potentiometer replacement in new designs
End-To-End Resistance	LCD panel V
5kΩ, 10kΩ, 50kΩ, 100kΩ	СОМ
Compact SOT23-8 (2.9 mm X 3 mm) Package	LCD panel brightness and contrast control
I2C Compatible Interface	Transducer adjustment of pressure, temperature, position, chemical, and optical sensors
Extra Package Address Decode Pin A0	RF amplifier biasing
Power On Reset To Midscale	Automotive electronics adjustment
Single Supply +2.7 V To +5.5 V	Gain control and offset adjustment
Low Temperature	
Coefficient 35 ppm/°C	
Low Power,>	

Wide Operating Temperature -40° C To $+125^{\circ}$ C



Related Products



AD5292BRUZ-20

Analog Devices, Inc 14TSSOP



AD5242BRZ10

Analog Devices, Inc SOIC-16



AD5142ABCPZ10-RL7 Analog Devices, Inc LFCSP-16



ovad



AD5293BRUZ-20

Applag Daviage 1

Analog Devices, Inc SOIC-24

AD5254BRUZ10

Analog Devices, Inc TSSOP20



AD8400ARZ10

Analog Devices, Inc

SOIC-8



AD5270BRMZ-20

Analog Devices, Inc MSOP-10