



Data Sheet

LED DRVR 1Segment 9V/12V/15V/18V/24V

Manufacturers <u>Microchip Technology</u>, Inc

Package/Case SOIC-8

Product Type Power Management ICs

RoHS

Lifecycle



Images are for reference only

Please submit RFQ for HV9961LG-G or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The HV9961 is an average current mode control LED driver IC operating in a constant off-time mode. Unlike HV9910B, this control IC does not produce a peak-to-average error, and therefore greatly improves accuracy, line and load regulation of the LED current without any need for loop compensation or high-side current sensing. The output LED current accuracy is $\pm 3\%$. The IC is equipped with a current limit comparator for hiccup-mode output short circuit protection. The HV9961 can be powered from an 8.0 - 450V supply. A PWM dimming input is provided that accepts an external control TTL compatible signal. The output current can be programmed by an internal 275mV reference, or controlled externally through a 0 - 1.5V dimming input.HV9961 is pin-to-pin compatible with HV9910B and it can be used as a drop-in replacement for many applications to improve the LED current accuracy and regulation.

Features

Fast average current control

Programmable constant off-time switching

Linear dimming input

PWM dimming input

Output short circuit protection with skip mode

Ambient operating temperature -40°C to +125°C

Pin-compatible withthe HV9910B



Related Products



HV9961NG-G

Microchip Technology, Inc SOP-16



HV9910BNG-G

Microchip Technology, Inc SOIC-16



MCP1631HV-330E/ST

Microchip Technology, Inc TSSOP-20



MCP1631HV-330E/SS

Microchip Technology, Inc SSOP-20



HV9910BLG-G

Microchip Technology, Inc SOIC-8



HV9861ALG-G

Microchip Technology, Inc SOIC-8



MCP1631HVT-500E/ST

Microchip Technology, Inc TSSOP-20



MCP1631VHV-330E/ST

Microchip Technology, Inc TSSOP-20