

LTC2855IGN#PBF

Data Sheet

3.3V 20Mbps RS485/RS422 Transceiver with Integrated Switchable Termination; Package: SSOP; No of Pins: 16; Temperature Range: -40°C to +85°C

Manufacturers	Analog Devices, Inc	a har har a second s
Package/Case	SSOP16	And the second s
Product Type	Interface ICs	
RoHS	Pb-free Halide free	
Lifecycle		Images are for reference only
Please submit RFO	for LTC2855IGN#PBF or <u>Email to us: sales@ovaga.com</u> Wo	e will contact you in 12 hours. RFO

General Description

The LTC2854 and LTC2855 are low power, 20Mbps RS485/RS422 transceivers operating on 3.3V supplies. The receiver includes a logic-selectable 120 Ω termination, one-eighth unit load supporting up to 256 nodes per bus (C-, I-Grade), and a fail-safe feature that guarantees a high output state under conditions of floating or shorted inputs.

The driver maintains a high output impedance over the entire common mode range when disabled or when the supply is removed. Excessive power dissipation caused by bus contention or a fault is prevented by current limiting all outputs and by a thermal shutdown.

Enhanced ESD protection allows the LTC2854 to withstand ± 25 kV (human body model) and the LTC2855 to withstand ± 15 kV on the transceiver interface pins without latchup or damage.

Part NumberDuplexPackageLTC2854HalfDFN-10LTC2855FullSSOP-16, DFN-12

Features

Integrated, Logic-Selectable 120Ω Termination Resistor

3.3V Supply Voltage

20Mbps Maximum Data Rate

No Damage or Latchup Up to ± 25 kV HBM

High Input Impedance Supports 256 Nodes (C-, I-Grade)

Operation Up to 125°C (H-Grade)

Guaranteed Fail-safe Receiver Operation Over the Entire Common Mode Range

Current Limited Drivers and Thermal Shutdown

Delayed Micropower Shutdown: 5µA Maximum (C-, I-Grade)

Power Up/Down Glitch-Free Driver Outputs

Low Operating Current: 370µA Typical in Receive Mode

Compatible with TIA/EIA-485-A Specifications

Available in 10-Pin 3mm × 3mm DFN, 12-Pin 4mm × 3mm DFN and 16-Pin SSOP Packages

Related Products



LTC4300A-11MIS8#PBF Analog Devices, Inc MSOP8



LTC2870IFE#PBF Analog Devices, Inc TSSOP28







LTC2854HDD#PBF
Analog Devices, Inc

Analog Devices, Inc QFN-10



LTC2870IUFD#PBF Analog Devices, Inc 28-QFN

LTC6820IMS#PBF

Analog Devices, Inc MSOP16

LTM2881IV-3#PBF

Analog Devices, Inc LGA32

LTC2852IDD#PBF

Analog Devices, Inc DFN10

Application

Low Power RS485/RS422 Transceiver

Level Translator

Backplane Transceiver