

IPT012N08N5ATMA1

Data Sheet

Trans MOSFET N-CH 80V 300A Automotive 9-Pin(8+Tab) HSOF T/R

Manufacturers <u>Infineon Tec</u>

Infineon Technologies Corporation

Package/Case

PG-HSOF-8

Product Type

RoHS

Lifecycle



Images are for reference only

Please submit RFQ for IPT012N08N5ATMA1 or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

Infineon's OptiMOSTM power MOSFET in TO-Leadless package is optimized for high current applications up to 300 A, such as forklifts, light electric vehicles (LEV), power tools, point-of-loads (POL), telecom and e-fuses. Furthermore, the 60 percent smaller package size enables a very compact design. Compared to D²PAK 7-pin, TO-Leadless shows a substantial reduction in footprint of 30 percent. The 50 percent reduced height offers a significant advantage in narrow applications such as rack or blade servers.

Optimized for synchronous rectification

Ideal for high switching frequency

Output capacitance reduction of up to 44 %

 $R_{DS(on)}$ reduction of up to 44 %

Highest system efficiency

Reduced switching and conduction losses

Less paralleling required

Increased power density

Low voltage overshoot

Telecom

Server

Solar

Low voltage drives

Light electric vehicles

Adapter

Features

Optimized for synchronous rectification

Ideal for high switching frequency

Output capacitance reduction of up to 44%

R DS(on) reduction of up to 44%

Highest system efficiency

Reduced switching and conduction losses

Less paralleling required

Increased power density

Low voltage overshoot

Related Products



IPS511GTRPBF

Infineon Technologies Corporation



IPC50N04S5-5R8

Infineon Technologies Corporation



IPD50N08S4-13

Infineon Technologies Corporation



IPC90N04S5-3R6

Infineon Technologies Corporation



<u>IPC100N04S5L-1R9</u>

Infineon Technologies Corporation



<u>IPLU300N04S4-1R1</u>

Infineon Technologies Corporation



IPD60R280P7S

Infineon Technologies Corporation



IPC90N04S5L-3R3

Infineon Technologies Corporation